LA TM080NIP

120° Near Infrared Pointsource TO46 LED (850 nm)

LIGHT AVENUE
A Brand of Chips 4 Light GmbH

Light Avenue's TO46 LED series is designed for high power and high temperature applications. Due to the high quality chips used the maximum operating current can be extended considerably compared to other devices. Junctions temperatures up to 125° C can be applied. A highly automated production process ensures high volume capability and competitive pricing.

Features

- Optical power 0.6 mW
- Peak wavelength 850 nm
- Point Source Chip
- Aperture 80 micrometer
- High operating temperatures
- TO46 package

Dimensions



all dimensions in mm. Tolerance ±0, 2 except given ones
* at the bottom of the LED

Ordering information

ORDERING NUMBER	ORDERING DESCRIPTION
LA TM080NIP-0206-X	LED Component, TO46 , 835 - 865 nm, 0.32 - 1 mW, 80µm Emitting Area

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

LA TM080NIP

120° Near Infrared Pointsource TO46 LED (850 nm)

LIGHT AVENUE
A Brand of Chips 4 Light GmbH

Electro-optical characteristics ($T_A = 25°C$)[2]

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.[1]	MAX.	UNIT
Radiant power	Φ_e	$I_f = 20\,mA$	0.32	0.6	1	mW
Radiant intensity	I_e	$I_f = 20\,mA$		0.12		mW/sr
Forward voltage	V_F	$I_f = 20\,mA$	1.15	1.55	2.15	V
Peak wavelength	λ_{peak}	$I_f = 20\,mA$	835	850	865	nm
Spectral width	RMS	$I_f = 20\,mA$		25		nm
Beam Divergence Angle	θ	$I_f = 20\,mA$		120		°

Maximum ratings ($T_A = 25°C$)

PARAMETER	SYMBOL	CONDITION	MINIMUM	MAXIMUM	UNIT
Operating Current	$I_{f,max}$			20	mA
Operating Pulse Current	$I_{fp,max}$	$t_p = 10\mu s$, D = 2%		50	mA
Operating Temperature	T_{op}		-40	100	° C
Storage Temperature	T_{st}		-50	125	° C
Junction Temperature	T_j			125	° C
Reverse Voltage	V_R		10		V
Power Consumption	P_{tot}			200	mW

Thermal characteristics

PARAMETER	SYMBOL	VALUE	UNIT
Thermal resistance junction ambient	$R\Theta_{JA}$	350	K/W
Soldering temperature (3 seconds maximum)	T_{sold}	320	°C

Material data

DESCRIPTION	MATERIAL	FINISH
LED chip	AlGaAs	
Stem	Kovar	Au plated
Cap	NiFe	Ni-plated
Lead Pins	Kovar	Au plated
Window	Glass AR coated	

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Recommended Solderpad





all dimensions in mm. Tolerance ±0, 1 except given ones

Soldering

METHOD	SOLDERING CONDITIONS	REMARK (VALID FOR TTW AND LEAD FREE SOLDERING)
TTW soldering	Bath temperature 250°C, Immersion time: within 5 sec.	Soldering according to IEC-61760-1 TTW
Soldering iron	30W or smaller, temperature at tip of iron maximum 300°C, soldering time within 3 sec.	During soldering take care not to press the tip of iron against the lead. To prevent heat from being transferred directly to the lead hold the lead with a pair of tweezers while soldering.

Actual solder profile is very much depending on wave type, machine configuration, geometrical configuration, board shape etc. It is strongly recommended to optimize and evaluate the actual soldering conditions carefully for each individual project before releasing the soldering process.

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Important Usage and Application Information

Lead free product - RoHS compliant.
All products, product specifications and data to improve reliability, function, design or otherwise are subject to change without notice. The information describes the type of component and shall not be considered as assured characteristics.
Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.
The light output of the products may cause injuries to human eyes in circumstances where the products are viewed directly with unshielded eyes. LEDs can emit highly concentrated light which can be hazardous to the human eye. Products which incorporate these devices have to follow the safety precautions given in IEC 60825-1 and IEC 62471.

Handling and Storage Conditions

This product is sensitive to electrostatic discharge (ESD).
Storage ambient conditions for all LEDs in sealed packages must be within $T_A = 10...40°C$ and relative humidity < 60%.

Packing

LEDs are packaged in trays. Labels for identification are placed on the box. The label shows company name and address, LED type, quantity and lot number. The box is hermetically sealed in a plastic bag for shipment.

Returns and Complaints

For complaints and returns of material a RMA-number is necessary. Samples for analysis purposes can be send to us without credit.

Shipping Conditions

If not otherwise arranged, the "General Terms of Business of Chips 4 Light GmbH" apply for any shipment. If this document is not familiar to you, please request it at our nearest sales office.

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Disclaimer
Attention please!
Components used in life-support devices or systems must be expressly authorized for such purpose!
Critical components[3] may only be used in life-support devices[4] or systems with the express written approval by us.
Chips 4 Light GmbH, its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Chips 4 Light makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Chips 4 Light disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Statements regarding the suitability of products for certain types of applications are based on Chips 4 Light 's knowledge of typical requirements that are often placed on Chips 4 Light 's products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Chips 4 Light 's terms and conditions of business, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, Chips 4 Light 's products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Chips 4 Light product could result in personal injury or death. Customers using or selling Chips 4 Light products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Chips 4 Light personnel to obtain written terms and conditions regarding products designed for such applications. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Chips 4 Light. Product names and markings noted herein may be trademarks of their respective owners.

Published by:
Chips 4 Light GmbH
Am Kuehlen Kasten 8
93161 Sinzing
Germany
www.chips4light.com
info@chips4light.com
©All Rights Reserved

[1]Due to the special conditions of the manufacturing processes of lasers, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
[2]Light Measurements are done with an accuracy of ±15%. Voltage and wavelength are measured with an accuracy of ± 0.1 V and ± 1 nm. Correlation to customer's equipment and products is required.
[3]A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or the effectiveness of that device or system.
[4]Life support devices or systems are intended(a) to be implanted in the human body,or(b) to support and/or maintain and sustain human life.If they fail, it is reasonable to assume that the health and the life of the user may be endangered..

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.