LA PD28AP3

Premium Edition Ambient light PIN photodiode 28 mil

LIGHT AVENUE
A Brand of Chips 4 Light GmbH

Light Avenue Premium Edition detector series is designed for high performance consumer applications. This chip is a high sensitive PIN photodiode chip with 0.34 mm^2 sensitive area detecting visible light similar to the human eye and a peak sensitivity at 560 nm. Anode and cathode are located at the top of the die.

Features

- High sensitivity silicon PIN photodiode
- Radiant sensitive area: 0.34 mm^2
- Suitable for visible light



Delineation



Mechanical characteristics

DESCRIPTION		MINIMUM	TYPICAL[1]	MAXIMUM
Chip size	(µm)	660	720	780
Chip height	(µm)	170	200	230
Bond pad diameter	(µm)	100	120	140
Left contact		Anode (p), AlSi		
Right contact		Cathode (n), NiV-Ag		
Die attach		Epoxy bonding		

Copyright , Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Electro-optical characteristics ($T_A = 25°C$)[2]

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.[1]	MAX.	UNIT
Breakdown voltage	V_{BR}	$I_R = 100\,\mu A$ $E_e = 0\,mW/cm^2$	16			V
Reverse dark current	I_{r0}	$V_R = 10\,V$ $E_e = 0\,mW/cm^2$		0.1	2	nA
Junction capacitance	C_D	$V_R = 3\,V$ $E_e = 0\,mW/cm^2$ $f = 1\,MHz$		35		pF
Reverse light current	I_{ra}	$V_R = 5\,V$ CIE illuminant A $E_v = 100\,lux$		0.87		µA
Maximum sensitivity	λ_p			560		nm
Spectral bandwidth	$\lambda_{0.5}$			430...700		nm
Rise and fall time	t_r, t_f	$V_R = 5\,V$ $\lambda = 515\,nm$ $R_L = 50\,\Omega$		100		ns

Maximum ratings ($T_A = 25°C$)[3]

PARAMETER	SYMBOL	VALUE	UNIT
Operating temperature range	T_{op}	-40...100	°C
Junction temperature	T_j	100	°C

Copyright , Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Typical characteristics graphs

Diode Capacitance vs. Reverse Voltage
(T_A = 25°C)



Relative Spectral Sensivity vs. Wavelength
(T_A = 25°C)



Copyright , Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Handling and Storage Conditions

Storage time for wafers in sealed condition is not limited by the die itself, but may be limited by the adhesion of the blue foil (storage ambient conditions: $T_a = 15 \ldots 30°C$; relative humidity: < 60%, vertical storage). Therefore we ship the dice without any limitation of shelf life. Customer has to make sure that there is no glue from the adhesive foil on the backside either by a die shear test or by visual inspection of the backside before production. The hermetically sealed shipment lot shall be opened under temperature and moisture controlled cleanroom environment only. Customers have to follow the according rules for desposition as the material can be hazardous for humans and the environment. Dice have to be handled ESD sensitive.

Packing

Chips are placed on a blue foil inside a 6 inch ring or alternatively on a blue foil (mylar) only. For shipment the wafers of a shipment lot are arranged to stacks. Please use the recycling operators familiar to you. If required you can ask for our help. Please get in touch with your nearest sales office. By agreement we will take packing material back, if sorted. Transport costs of any kind must be paid by customers. For packing material that is returned to us unsorted or which we are not obliged to accept, any costs incurred will be invoiced to you.

Design Objectives

The chip design was developed and released based on the producer's standard assembly procedures and packaging. Bond strength properties are in accordance to MIL-STD-750D, method 2037. Whether the chip fits to the customer's products with its according die and wire bond procedures and packaging must be evaluated by the customer himself. If workability problems arise after this release a mutually conducted problem solving procedure has to be set up, if the chips are suspected of contributing to the problems.The chips are produced with best effort, but on chip level a subset of the chip characteristics can be determined only. Performance of the chip in the customer's products can only be determined by the customer himself.

Returns and Complaints

For complaints and returns of material a RMA-number is necessary. Samples for analysis purposes can be sent to us without credit.

Shipping Conditions

If not otherwise arranged, the "General Terms of Business of Chips 4 Light GmbH" apply for any shipment. If this document is not familiar to you, please request it at our nearest sales office.

Copyright , Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Disclaimer
Attention please!

- **Components used in life-support devices or systems must be expressly authorized for such purpose!**
  Critical components[4] may only be used in life-support devices[5] or systems with the express written approval by us.
- All products, product specifications and data to improve reliability, function, design or otherwise are subject to change without notice .
- Chips 4 Light GmbH, its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Chips 4 Light makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Chips 4 Light disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Statements regarding the suitability of products for certain types of applications are based on Chips 4 Light's knowledge of typical requirements that are often placed on Chips 4 Light's Light Avenue products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Chips 4 Light's terms and conditions of business, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, Chips 4 Light's Light Avenue products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Chips 4 Light's Light Avenue product could result in personal injury or death. Customers using or sellingChips 4 Light products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Chips 4 Light personnel to obtain written terms and conditions regarding products designed for such applications. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Chips 4 Light GmbH. Product names and markings noted herein may be trademarks of their respective owners.
- The information describes the type of component and shall not be considered as assured characteristics. Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.
- Lead free product - RoHS compliant.
- The quality level of the final visual inspection shall comply to an AQL of 1.0 (according to MIL-STD-105E, level II), if the customer performes an incoming visual inspection of a shipment.

Copyright , Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

- All chips are checked according to the producer's specification of the visual inspection. If this document is not familiar to you, please request it at our nearest sales office.

Published by:
Chips 4 Light GmbH
Am Kuehlen Kasten 8
93161 Sinzing
Germany
www.chips4light.com
info@chips4light.com
All Rights Reserved

[1]Due to the special conditions of the manufacturing processes of detectors, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.

[2]Measurements are done on sample basis with an accuracy of $\pm$15%. Correlation to customer's equipment and products is required.

[3]Maximum ratings are package dependent and may differ from package to package.

[4]A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or the effectiveness of that device or system.

[5]Life support devices or systems are intended(a) to be implanted in the human body,or(b) to support and/or maintain and sustain human life.If they fail, it is reasonable to assume that the health and the life of the user may be endangered.

Copyright , Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.