LA PL150RBD

120° Royal blue Point Source LED (470 nm)

A Brand of Chips 4 Light GmbH

The point source 0402 LED is designed for applications, where an extremely small emission point without any bondwires is needed. The LED is produced by using a high efficiency LED flip chip mounted on a small black ceramic aluminum oxide submount.The point source LED is easy to handle and IR-reflow solderable.The chip placement accuracy relative to the package is very high.

Features

- Optical power 12 mW
- Peak wavelength 470 nm
- High optical efficiency
- Point source chip
- High optical precision
- Black SMT package



Dimensions



all dimensions in mm. Tolerances ±0.1

Ordering information

ORDERING NUMBER	ORDERING DESCRIPTION
LA PL150RBD-1619-X	LED Component, 1005 SMD ceramic , 450 - 480 nm, 8 - 20 mW, 140° Viewing Angle

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

LA PL150RBD

120° Royal blue Point Source LED (470 nm)

LIGHT AVENUE
A Brand of Chips 4 Light GmbH

Electro-optical characteristics ($T_A = 25°C$)[2]

PARAMETER	SYMBOL	CONDITION	MIN.	TYP.[1]	MAX.	UNIT
Radiant power	Φ_e	$I_f = 20\,mA$	8	12	20	mW
Radiant intensity	I_e	$I_f = 20\,mA$		3		mW/sr
Forward voltage	V_F	$I_f = 20\,mA$	2,6	3	3,6	V
Peak wavelength	λ_{peak}	$I_f = 20\,mA$	450	470	480	nm
Spectral width	RMS	$I_f = 20\,mA$		21		nm
Beam Divergence Angle	θ	$I_f = 20\,mA$		120		°

Maximum ratings ($T_A = 25°C$)

PARAMETER	SYMBOL	CONDITION	MINIMUM	MAXIMUM	UNIT
Operating Current	$I_{f,max}$			50	mA
Operating Pulse Current	$I_{fp,max}$	$t_p = 10\mu s$, D = 2%		200	mA
Operating Temperature	T_{op}		-40	100	° C
Storage Temperature	T_{st}		-40	100	° C
Junction Temperature	T_j			125	° C
Reverse Voltage	V_R		5		V
Power Consumption	P_{tot}			180	mW

Recommended Solderpad



Soldering

The device is suitable for standard reflow soldering according to JEDEC J-STD-020. Peak temperature between 245 and 260°C.

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Important Usage and Application Information

Lead free product - RoHS compliant.
All products, product specifications and data to improve reliability, function, design or otherwise are subject to change without notice. The information describes the type of component and shall not be considered as assured characteristics.
Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.
The light output of the products may cause injuries to human eyes in circumstances where the products are viewed directly with unshielded eyes. LEDs can emit highly concentrated light which can be hazardous to the human eye. Products which incorporate these devices have to follow the safety precautions given in IEC 60825-1 and IEC 62471.

Handling and Storage Conditions

This product is sensitive to electrostatic discharge (ESD).
Storage ambient conditions for all LEDs in sealed packages must be within $T_A = 10...40°C$ and relative humidity < 60%. LEDs in opened packages must be used within 2 weeks after opening. Storage time under the conditions above in sealed packages must not exceed 24 months.

Packing

LEDs are packaged automatically on reels and packed into paperboard containers. Labels for identification are placed on the box. The label shows company name and address, LED type, quantity and lot number. The box is hermetically sealed in a plastic bag for shipment.

Returns and Complaints

For complaints and returns of material a RMA-number is necessary. Samples for analysis purposes can be send to us without credit.

Shipping Conditions

If not otherwise arranged, the "General Terms of Business of Chips 4 Light GmbH" apply for any shipment. If this document is not familiar to you, please request it at our nearest sales office.

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.

Disclaimer
Attention please!
Components used in life-support devices or systems must be expressly authorized for such purpose!
Critical components[3] may only be used in life-support devices[4] or systems with the express written approval by us.
Chips 4 Light GmbH, its affiliates, agents, and employees, and all persons acting on its or their behalf, disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. Chips 4 Light makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Chips 4 Light disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Statements regarding the suitability of products for certain types of applications are based on Chips 4 Light 's knowledge of typical requirements that are often placed on Chips 4 Light 's products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Chips 4 Light 's terms and conditions of business, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, Chips 4 Light 's products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Chips 4 Light product could result in personal injury or death. Customers using or selling Chips 4 Light products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Chips 4 Light personnel to obtain written terms and conditions regarding products designed for such applications. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Chips 4 Light. Product names and markings noted herein may be trademarks of their respective owners.

Published by:
Chips 4 Light GmbH
Am Kuehlen Kasten 8
93161 Sinzing
Germany
www.chips4light.com
info@chips4light.com
©All Rights Reserved

[1]Due to the special conditions of the manufacturing processes of lasers, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
[2]Light Measurements are done with an accuracy of ±15%. Voltage and wavelength are measured with an accuracy of ± 0.1 V and ± 1 nm. Correlation to customer's equipment and products is required.
[3]A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or the effectiveness of that device or system.
[4]Life support devices or systems are intended(a) to be implanted in the human body,or(b) to support and/or maintain and sustain human life.If they fail, it is reasonable to assume that the health and the life of the user may be endangered..

Copyright ©, Chips 4 Light GmbH. All Rights Reserved. Content is subject to change without notice.